

KS M 6060 Thinner, Class3

Lacquer Thinner

Technical data Sheet



1. Product Description

KSM 6060 Thinner class3 is clear, colorless. ready to spray blending Thinner used to Lacquer paint

2. Recommended Uses

Thinner for Lacquer paint

3. Features

Classification		Class 3
Specific gravity		about 0.84
Distillation	I.B.P (0°C)	more than 86
	Recovery at 98°C (%)	below 5
	Recovery at 104°C (%)	below 46
	50% Recovery Temperature (°C)	-
	90% Recovery Temperature (°C)	-
	Dry point	below 130
Flash point		-
Mixed Aniline point		-
Ketone & Ester (%)		more than 35
Non volatile Matter		below 0.02
Appearance		Clear, Colorless
Spot test		No Staining
Copper Corrosion Resistance		No Darkening
Acid value(KOH mg/g)		below 0.3

The Information and Recommendations in This TDS are based upon Tests and are subject to change without prior Notice.

KS M 6060 Thinner, Class3

Lacquer Thinner



4. Precautions

- Read the Material Safety Data Sheet.
- Avoid contact with eyes.
- Keep out of reach of children.
- Use only in well ventilated areas.
- Do not intentionally breathe vapour.
- Keep away from flames or sparks.
- If in contact with eyes, rinse thoroughly with clean water.